




PRODUCT DATA SHEET



F3405



METSTRIP SV3405

BRUSH APPLICATION PAINT STRIPPER

PRODUCT DESCRIPTION

METSTRIP SV3405 is a high-speed brush application paint remover designed to remove quickly and cleanly most industrial paint finishes, lacquers and varnishes.

FEATURES & BENEFITS

May be brush applied to both horizontal and vertical surfaces.
Effective on most finishes, including stove enamels and non-convertible air dry finishes.
Non-flammable.
Low evaporation rate for maximum activity period.

DIRECTIONS FOR USE

Use as supplied at room temperature.
Apply in thick layers and allow to soak into the paint surface being removed.
Wait until the paint lifts and bubbles.
A second application is sometimes required.
Some non-convertible finishes will soften and may need to be scraped or wiped off.
Finally rinse off with water or solvent to remove all traces of paint residue and excess stripper prior to drying and repainting.
Always rinse wood with solvents as water may cause wood grain to swell.

Equipment: Brush applied to most surfaces. Beware of plastic and light magnesium alloys.
Rubber components and seals will also swell if left in contact with METSTRIP SV3405 for short periods.

Handling: Wear gloves, eye protection, respiratory protection when handling.
Do not smoke and do not apply to hot surfaces.
Do not inhale vapour. Use in a well ventilated area or use local exhaust ventilation.

F3405 – METSTRIP SV3405 falls under the European Regulation for the Restrictions on the Marketing and Use of Dichloromethane (Council Directive 76/769/EEC).

Manufacturing site and registered office

Orapi Applied Limited
Spring Road, Smethwick, West Midlands
B66 1PT, United Kingdom
Tel: +44 (0) 121 525 4000
Fax: +44 (0) 121 525 4919
Info@orapiapplied.com


1 / 2

F3405 - TDS METSTRIP SV3405 – 25/07/19

ORAPI® cannot know about every application for which the products are used nor their conditions of use. ORAPI® cannot be held responsible for the suitability of the products for a given use or a specific purpose. The information contained here can on no account be a substitute for the preliminary tests which are essential and which must be carried out in order to check the suitability of the product to each specific case.



PRODUCT DATA SHEET



F3405

PHYSICAL CHARACTERISTICS

Appearance:	Thick colourless opaque gel
Specific Gravity:	1.220
Solubility:	Most organic solvents. Not soluble in water but emulsifies when rinsed away.
Initial boiling point:	40°C

SPECIAL STORAGE

Store in a cool place away from food stuff and direct sunlight.
Containers should be stored upright.
Containers should be kept tightly closed and opened with caution.

HEALTH AND SAFETY

Refer to Material Safety Data Sheet for further information.

PACKAGING

Pack size:	F3405-25	1 x 25L
	P3405-2X5	2 x 5L

Manufacturing site and registered office

Orapi Applied Limited
Spring Road, Smethwick, West Midlands
B66 1PT, United Kingdom
Tel: +44 (0) 121 525 4000
Fax: +44 (0) 121 525 4919
Info@orapiapplied.com

2 / 2

F3405 - TDS METSTRIP SV3405 – 25/07/19

ORAPI® cannot know about every application for which the products are used nor their conditions of use. ORAPI® cannot be held responsible for the suitability of the products for a given use or a specific purpose. The information contained here can on no account be a substitute for the preliminary tests which are essential and which must be carried out in order to check the suitability of the product to each specific case.